



	18423 FWTD-50-HT	18262 FWTD-70-HT	18424 FWTRD-100-HT
Capacity (Distributed)	48,500 lbs.	70,000 lbs.	100,000 lbs.
Concentrated Load		50,000 lbs. in 10'	70,000 lbs. in 10'
Base Trailer Weight (Varies depending on Options)	17,200 lbs.	19,000 lbs.	21,940 lbs.
Frame Construction: Fabricated design A-656 high tensile	X	X	X
Crossmembers Spacing	5"-12 & 16" O.C.	8" -12" O.C.	8" -12" O.C.
Hitch: King Pin type 150,000 PSI ultimate strength, 115,000 yield	X	X	X
Landing Gear: 2 Speed 70,000 lb., 100,000 lb. static load	X	X	X
Load Securement: 2-way chain slot/stake pocket system	18 (9 per side)	24 (12 per side)	28 (14 per side)
Hydraulic System: Wet kit PTO hydraulic operation with controls at gooseneck	X	X	X
Storage Compartment: 2 each Storage Compartments in Upper Deck	X	X	X
Winch : 20,000 lb. Hydraulic 2-stage Planetary Gear with recessed cable rollers	None	X	X
Axles: 5 in. round 1/2" wall thickness, 71-1/2" track and 40" spring centers	2- 20,000 lbs.		
Axles: 5 in. round 5/8" wall thickness, 71 1/2" track		2- 25,000 lbs.	3- 25,000 lbs.
Hubs: Oil bath type with Unimount Hub and drum, 8 on 275mm bolt circle	X	X	X
Brakes: 12-1/4" x 7-1/2" s-cam full air brakes with maxi spring brakes on both axles, automatic slack adjusters, equipped with 2S/2M ABS	X	X	X
Drums: Steel Outboard type	X	X	X
Suspension	Hutch H-9700	Ridewell 240 Air	Ridewell 240 Air
Wheels: 17.5" x 6.75" Uni-mount 8 on 275mm bolt circle	X	X	X
Tires: 17.5 Load Range H	215/75R	235/75R	235/75R
Electrical: Trucklite 88 series modular system w/ rubber isolated, LED lighting	X	X	X
Finish Preparation: Sandblast	X	X	X
Base Coating: Two-component epoxy primer sealer	X	X	X
Finish Coating: Two-component urethane enamel top coat	X	X	X
Decking: Fasteners at all crossmembers	2" No.1 grade Fir	2 1/8" Oak	2 1/8" Oak

Capacities and Specifications can vary depending on Optional Equipment >>> Specifications subject to change without notice

Authorized Dealer:



The TrailMax *HT Series* offers a broad range of uses. From multiple piece loads to the over size heavy haul applications, it provides safe loading with one person operation. The air ride suspension provides a smooth and stable ride. A 20,000 lb. winch makes for ease of loading that inoperable equipment.

At TrailMax we pride ourselves on building quality equipment trailers that provide...

Maximum Performance
Maximum Reliability, and
Maximum Return on Investment



www.TrailMax.com



5-Year Structural Warranty on all TrailMax Trailers

Fifth Wheel Hydraulic Tail Trailers



The HT Series features a fold out tail with a knife edge design, combined with the air ride suspension dump valve, to provide the lowest load angle.

By design, the HT Series hydraulic tail will outperform other similar designs when lifting and transporting on the tail section.

With two simple levers, the hydraulic tail extends to 12', then lowers to the ground to provide a zero clearance approach transition from ground surface to ramp.

The HT Series hydraulic tail can be raised to dock height for dock loading applications.

The HT Series hydraulic tail trailer comes standard with steel traction plate full length on the ramp.

Fifth Wheel HT Series



Aluminum Wheels



Recessed D-Rings



Hubometer



12" Outriggers



Stake Pocket/Chain Slots on 24" Centers



20,000 lb. Hydraulic Winch (on select models)

Features & Benefits



2 ea. Storage Compartment in Upper Deck



Hydraulic Controls at Gooseneck



Traction Surface on Ramp



Air Ride Suspension with Dump Valve (on select models)

The TrailMax Advantage

Superior Quality – TrailMax trailers are built to last. From the conception in the design process and throughout the manufacturing, every step is taken to ensure durability for years of rugged use. All of our trailer are designed with the end-user in mind.

Construction – Unlike conventional I-beam or channel iron construction, TrailMax trailers are engineered with top quality tensile steel construction throughout. With steel components designed to maintain consistent tolerances to assure accuracy during the assembly process.

Components – Major brand name components are used in the manufacturing process. Components that live up to the demands and performance we expect from each of our TrailMax products.

Quality Assurance – TrailMax Trailers maintains the highest quality standards in the industry. Process controls are maintained to assure consistency throughout the manufacturing process. Periodic testing is performed to assure that standards are met while constantly identifying opportunity for continual design and process improvement.

Options & Accessories Available for Fifth Wheel HT Series

12" Outriggers

4S 2M ABS

D-Rings

Weld-On Combination Winch

Amber Strobe/TailLight

Custom Paint

Canadian Axles Specs.

Hydraulic Landing Gear

2-Function Wireless Remote

Back Up Lights

Spare Tire

Hubometer

Aluminum Wheels



Hydraulic Landing Gear



Custom Paint



Expandable Outriggers



Belt Winches