



		17809 GTD-24-HT	18441 TD-24-HT
Capacity (Distributed)		17,740 lbs.	17,810 lbs.
G.V.W.R.		26,000 lbs.	26,000 lbs.
Base Trailer Weight		8,260 lbs.	8,190 lbs.
Frame Construction	Tubular subframe with high tensile perimeter rails	Std	Std
Crossmembers	4" Tubular Crossmembers on 16" Centers	Std	Std
Hitch	2-5/16" ball coupler, adjustable	Std	Pintle Hitch
Landing Gear	12,000 lb. capacity with drop foot	Std	Std
Safety Chains	2 each 3/8" x 36" Grade 70 high test cadmium plated w/slip hooks & safety latches	Std	Std
Load Securement	14 each (7 per side) 2-way chain slot/stake pocket system	Std	Std
Hydraulic System	Self contained electric/hydraulic	Std	Std
Axles	2 each 12,000 lb. capacity, 5 in. round 74-1/2" track and 46" spring centers	Std	Std
Hubs	Oil bath type, 8 on 6.5 bolt circle 5/8" cone nuts	Std	Std
Brakes	12-1/4" x 3-1/2" electric brakes both axles with 12 volt sealed breakaway system	Std	Std
Suspension	3-point with axle alignment capability	Std	Std
Wheels	16" x 6.00" 8 hole disc type 6.5 bolt circle	Std	Std
Tires	235/80R 16 radial load range E	Std	Std
Finish Preparation	5 stage Acid pre-treatment wash with Phosphate & Sealer	Std	Std
Base Coating	Two-component epoxy primer sealer	Std	Std
Finish Coating	Two-component urethane enamel top coat	Std	Std
Electrical	Trucklite 88 series modular system with rubber isolated, sealed beam LED lighting	Std	Std
Decking	2" rough surface No. 1 grade Fir with fasteners at all crossmembers	Std	Std

Capacities and Specifications can vary depending on Optional Equipment >>> Specifications subject to change without notice.



The TrailMax GTD-24-HT and the TD-24-HT offer a broad range of uses. They work well for multiple-piece loads, including loading & transporting on the hydraulic tail. They provide safe and easy loading & unloading with one person operation. Optional winch makes for ease of loading that inoperable equipment. Multiple anchor points for load securement choices.

At TrailMax we pride ourselves on building quality equipment trailers that provide...

Maximum Performance
Maximum Reliability, and
Maximum Return on Investment



www.TrailMax.com



5-Year Structural Warranty on all TrailMax Trailers



The HT Series features a fold out tail with a knife edge design, to provide the lowest load angle and zero approach unlike comparable brands.



By design, the HT Series hydraulic tail will outperform other similar designs when lifting and transporting on the ramp section.



With two simple levers, the hydraulic tail extends out, then lowers to the ground to provide a zero clearance approach transition from ground surface to ramp.



The HT Series hydraulic ramp can be raised to dock height for dock loading applications.

The HT Series hydraulic tail trailer comes standard with steel diamond plate entry tail on the ramp.

Features & Benefits



Stake Pocket/Chain Slots on 24" Centers



Self Contained 12 Volt Power Unit



Chain & Binder Storage

The TrailMax Advantage

Superior Quality – TrailMax trailers are built to last. From the conception in the design process and throughout the manufacturing, every step is taken to ensure durability for years of rugged use. All of our trailers are designed with the end-user in mind.

Construction – Unlike conventional I-beam or channel iron construction, TrailMax trailers are engineered with top quality tensile steel construction throughout. With steel components designed to maintain consistent tolerances to assure accuracy during the assembly process.

Components – Major brand name components are used in the manufacturing process. These components live up to the demands and performance we expect from each of our TrailMax products.

Quality Assurance – TrailMax Trailers maintain the highest quality standards in the industry. Process controls are maintained to assure consistency throughout the manufacturing process. Periodic testing is performed to assure that standards are met while constantly identifying opportunities for continual design and process improvement.

MAXimum Performance
MAXimum Reliability, and
MAXimum Return on Investment

Highly Optioned GTD-24-HT



Custom Paint
 Detail Package
 Spare Tire Carrier
 LED Lights

Hydraulic Jack
 Extend Rear Deck
 Recessed D-Rings

Visit trailmax.com/video for action video of the hydraulic ramp.

Medium HT Series

Options & Accessories Available for Medium HT Series

D-Rings
 LED Lights
 6" Extended Gooseneck Height
 Storage Tray in Gooseneck
 Weld-On Combination Winch

Custom Paint
 Spare Tire Carrier
 Canadian Axles Specs.
 Self Cont. Hydraulic Power
 48" Underbody Toolbox

Back Up Lights
 Hubometer
 Aluminum Wheels
 Mid Ship Turn Signal
 Amber Strobe/TailLight



Hydraulic Landing Gear



D-Rings



Hubometer



Belt Winches



48" Underbody Toolbox



Custom Paint



Spare Tire Carrier



Electric Winch