



	18416 TD-24-PR	18440 TD-24-PR	17704 GTD-24-PR
Gross Vehicle Weight Rating	26,000 lbs.	26,000 lbs.	26,000 lbs.
Capacity (Distributed)	17,180 lbs.	16,890 lbs.	16,820 lbs.
Base Trailer Weight (Varies depending on Options)	8,820 lbs.	9,110 lbs.	9,180 lbs.
Frame Construction - Tubular subframe with high tensile perimeter rails	X	X	X
Crossmembers - 4" Tubular Crossmembers on 16" Centers	X	X	X
Hitch	Drawbar Eye	Drawbar Eye	2-5/16" Ball
Landing Gear - 12,000 lb. capacity with drop foot	X	X	X
Safety Chains - 2 each 3/8" x 36" Grade 70 high test cadmium plated with slip hooks and safety latches	X	X	X
Load Securement - 2-way chain slot/stake pocket system	14 (7 per side)	14 (7 per side)	14 (7 per side)
Hydraulic System - Self contained electric/hydraulic	X	X	X
Tool Compartment - In tongue with lockable lid	X	X	N/A
Axles - 5 in. round 74-1/2" track and 46" spring centers	2-12,000 lbs.	2-12,000 lbs.	2-12,000 lbs.
Hubs - Oil bath type, 8 on 6.5 bolt circle 5/8" cone nuts	X	X	X
Brakes - 12-1/4" x 3-1/2" electric brakes both axles w/ 12 volt sealed breakaway system	X	N/A	X
Brakes - 12-1/4" x 5 1/2" s-cam full air brakes with maxi spring brakes on one axle, automatic slack adjusters, 2S/2M ABS	N/A	X	N/A
Suspension - 3-point with axle alignment capability	X	X	X
Wheels - 16" x 6.00" 8 hole disc type 6.5 bolt circle	X	X	X
Tires - 235/80R 16 radial load range E	X	X	X
Finish Preparation - Sandblast	X	X	X
Base Coating - Two-component epoxy primer sealer	X	X	X
Finish Coating - Two-component urethane enamel top coat	X	X	X
Electrical - Trucklite 88 series modular system with rubber isolated, LED lighting	X	X	X
Decking - 2" rough surface No. 1 grade Fir with fasteners at all crossmembers	X	X	X

Capacities and Specifications can vary depending on Optional Equipment >>> Specifications subject to change without notice

Authorized Dealer:



The TrailMax **PR Series** offers a broad range of uses. It features a low ramp angle of 8° for loading low clearance and gradeability challenged equipment. The ramp is lowered and raised hydraulically and provides safe loading with one person operation. Available in many different configurations and capacities.

TrailMax - we pride ourselves on building quality equipment trailers that provide...

Maximum Performance
Maximum Reliability, and
Maximum Return on Investment



www.TrailMax.com



5-Year Structural Warranty on all TrailMax Trailers

Power Ramp Trailers



The ramp stores in the vertical position and locked into position with an adjustable latch mechanism on each side to keep ramp secure, tight and rattle free during transport.



The PR Series ramp comes standard with a steel mesh surface that provides excellent traction while minimizing wind drag during transport.



The PR Series features a Bi-Fold design ramp that extends out to an 8° load angle hydraulically with the touch of a lever.



When in the load position, it provides a zero clearance approach transition from ground surface to ramp.

Standard Features



8 degree Load Angle



Self Contained 12 Volt Power Unit



Stake Pocket/Chain Slots



Storage Compartment

Options & Accessories



48" Underbody Tool Box



Rubber® Decking



Custom Paint



Recessed D-Rings



Belt Winch

The TrailMax Advantage

Superior Quality – TrailMax trailers are built to last. From the conception in the design process and throughout the manufacturing, every step is taken to ensure durability for years of rugged use. All of our trailers are designed with the end-user in mind.

Construction – Unlike conventional I-beam or channel iron construction, TrailMax trailers are engineered with top quality tensile steel construction throughout. With steel components designed to maintain consistent tolerances to assure accuracy during the assembly process.

Components – Major brand name components are used in the manufacturing process. These components live up to the demands and performance we expect from each of our TrailMax products.

Quality Assurance – TrailMax trailers maintain the highest quality standards in the industry. Process controls are maintained to assure consistency throughout the manufacturing process. Periodic testing is performed to assure that standards are met while constantly identifying opportunity for continual design and process improvement.

TrailMax Offers Alternative Ramp Configuration



Standard FBR Ramps

Our standard ramps offer a 14° load angle, with ramps adjustable for various track widths.

Options & Accessories Available for Medium PR

D-Rings
Recessed D-Rings
48" Underbody Toolbox
Weld-On Combination Winch
Mid Ship Turn Signal

Chock Blokes
Custom Paint
Rubber® Deck
Canadian Axles Specs.

Back Up Lights
Spare Tire
Hubometer
Amber Strobe/TailLight

Medium PR Series