



	18404 TD-20-FBR	18407 GTD-20-FBR	18405 TD-24-FBR	18406 TD-24-FBR	18408 GTD-24-FBR
GVWR (lbs.)	25,600	24,000	26,000	26,000	26,000
Capacity (Distributed) (lbs.)	19,440	17,640	19,660	19,590	19,300
Base Trailer Weight (lbs.)	6,160	6,630	6,340	6,410	6,700
Frame Construction - Tubular subframe with high tensile perimeter rails	X	X	X	X	X
Crossmembers - 4" Tubular crossmember on 16" centers	X	X	X	X	X
Hitch - 30,000 lb. capacity adjustable	drawbar eye	2 5/16" ball	drawbar eye	drawbar eye	2 5/16" ball
Landing Gear - 12,000 lb. capacity with drop foot	X	X	X	X	X
Safety Chains - 2 each Grade 70 high test cadmium plated with slip hooks and safety latches	3/8" X 36"	3/8" X 36"	3/8" X 36"	3/8" X 36"	3/8" X 36"
Load Securement - 12 each (6 per side) 2 way chain slot/stake pocket system	X	X	X	X	X
Tool Compartment - In tongue with lockable lid	X	No	X	No	X
Axles - 5in. round 74-1/2" track and 46" spring centers	2 -10K	2-10K	2-12K	2-12K	2-12K
Hubs - Oil bath type, 8 on 6.5 bolt circle 5/8" cone nuts	X	X	X	X	X
Brakes - Electric brakes both axles w/ 12 volt sealed breakaway system	12 1/4" x 3 1/2"	12 1/4" x 3 1/2"	12 1/4" x 3 1/2"		12 1/4" x 3 1/2"
Brakes - 12 1/4" X 5 1/2" s-cam full air brakes w/ maxi spring brakes on one axle, automatic slack adjusters, 2S/2M ABS				X	
Suspension - 3-point with axle alignment capability	X	X	X	X	X
Wheels - 16" x 6.00" 8 hole disc type 6.5 bolt circle	X	X	X	X	X
Tires - 235/80R 16" radial load range E	X	X	X	X	X
Finish Preparation - Sandblast	X	X	X	X	X
Base Coating - Two-component epoxy primer sealer	X	X	X	X	X
Finish Coating - Two-component urethane enamel top coat	X	X	X	X	X
Electrical - Trucklite 88 series modular system with rubber isolated, LED lighting	X	X	X	X	X
Decking - 2" rough surface No.1 grade Fir with fasteners at all crossmembers	X	X	X	X	X

Capacities and Specifications can vary depending on Optional Equipment >>> Specifications subject to change without notice

Authorized Dealer:



The TrailMax Medium FBR Series offers a broad range of uses for hauling track machines and wheel type equipment. The user friendly design provides the most economical way for loading and unloading equipment safely. It features multiple anchor points for securing the load for transport.

At TrailMax we pride ourselves on building quality equipment trailers that provide...

Maximum Performance
Maximum Reliability, and
Maximum Return on Investment



www.TrailMax.com

5-Year Structural Warranty on all TrailMax Trailers

Medium Beavertail Trailers

Trailmax has 2 additional model series in the FBR configuration



Heavy FBR

GVWR RANGES FROM 46,800 TO 66,980



Fifth Wheel FBR

GVWR RANGES FROM 50,000 TO 100,000

TrailMax Offers 3 Different Ramp Configurations



Standard FBR Ramps

Our standard ramps offer a 14° load angle, with ramps adjustable for various track widths.



Light-weight Steel FBR Ramps

We offer an 8° Beavertail with a longer ramp to provide a lower load angle for low clearance & hard to load equipment.



See Our Power Ramp Series

It features a hydraulic bi-fold design that extends to 8° with a zero approach transition from ground surface to ramp.

Features & Benefits



< Stake Pocket/Chain Slot
Provide Diverse Load
Securement Options



> Lockable storage compartment
in tongue area



< Spring Assist Ramps are
adjustable to within
16" of center



> Ramps store level with main
deck to provide additional load
space at rear of deck

The TrailMax Advantage

Superior Quality – TrailMax trailers are built to last. From the conception in the design process and throughout the manufacturing, every step is taken to ensure durability for years of rugged use. All of our trailers are designed with the end-user in mind.

Construction – Unlike conventional I-beam or channel iron construction, TrailMax trailers are engineered with top quality tensile steel construction throughout. With steel components designed to maintain consistent tolerances to assure accuracy during the assembly process.

Components – Major brand name components are used in the manufacturing process. Components that live up to the demands and performance we expect from each of our TrailMax products.

Quality Assurance – TrailMax Trailers maintains the highest quality standards in the industry. Process controls are maintained to assure consistency throughout the manufacturing process. Periodic testing is performed to assure that standards are met while constantly identifying opportunity for continual design and process improvement.

Options & Accessories Available for Medium FBR Series

Recessed D-Rings

48" Underbody Toolbox

Weld-On Combination Winch

Custom Paint

Chock Blocks

Canadian Axles Specs.

Back Up Lights

Spare Tire

Hubometer

Amber Strobe/TailLight



D-Rings



Hubometer



48" Underbody Toolbox



Custom Paint



Belt Winches